



NORTHERN STRANDS

Alloy Chain Fittings Grade 100


Welded Master Link, Grade 100

	Trade Size	Code	Dimensions			Weight/ea, lbs	Work Load Limit, lbs	Suited for chain size	
			Dia.	I.L.	I.W.			1 Leg	2 Leg
	1/2"	AX13	1/2"	4.33	2.36	0.75	4,700	9/32	7/32
	5/8"	AX16	5/8"	4.33	2.36	1.17	8,600	5/16	9/32
	3/4"	AX18	3/4"	5.31	2.95	1.76	12,900	3/8	5/16
	7/8"	AX22	7/8"	6.50	3.62	3.31	17,600	1/2	3/8
	1"	AX26	1"	7.09	3.94	5.07	30,000	5/8	1/2
	1-1/4"	AX32	1 1/4"	7.87	4.33	8.60	38,200	3/4	(n/a)
	1-1/2"	AX36	1 1/2"	10.24	5.51	14.00	50,200	7/8	5/8


Welded Master Link Assembly, Grade 100

	For Chain	Code	Dimensions						Weight/ea, lbs	Work Load Limit, lbs
			Dia.	I.L.	I.W.	D2	I.L.2	I.W.2		
	9/32"	AKX1813	3/4"	5.31	2.95	1/2	2.13	0.98	2.65	11,200
	5/16"	AKX2216	7/8"	6.50	3.62	5/8	2.76	1.34	5.07	15,200
	3/8"	AKX2618	1"	7.09	3.94	3/4	3.35	1.57	7.85	26,000
	1/2"	AKX3626	1-1/2"	10.24	5.51	1	5.51	2.56	22.05	43,400


Connecting Link, Grade 100

	For Chain	Code	Dimensions						Weight/ea, lbs	Work Load Limit, lbs
			A	C	O	R	P	S		
	9/32"	CLX07	0.63	0.79	0.75	2.01	0.39	0.35	0.26	4,300
	5/16"	CLX08	0.71	0.98	0.91	2.44	0.45	0.39	0.40	5,700
	3/8"	CLX10	0.91	1.18	1.06	2.83	0.50	0.50	0.73	8,800
	1/2"	CLX13	1.06	1.42	1.34	3.46	0.75	0.66	1.54	15,000
	5/8"	CLX16	1.30	1.57	1.54	4.06	0.83	0.83	2.51	22,600
	3/4"	CLX20	1.65	1.81	1.81	4.45	1.14	0.98	4.52	35,300
	7/8"	CLX22	1.93	2.17	2.28	5.24	1.18	1.10	6.83	42,700

Clevis Sling Hook, Grade 100 with forged latch

	For Chain	Code	Dimensions								Weight/ea, lbs	Work Load Limit, lbs
			A	A1	B	C	G	H	R	PxL		
	9/32"	CBX07SF	1.34	1.02	0.37	0.39	0.75	1.10	3.74	0.35*0.90	1.21	4,300
	5/16"	CBX08SF	1.34	1.02	0.37	0.39	0.75	1.10	3.74	0.35*0.90	1.21	5,700
	3/8"	CBX10SF	1.57	1.22	0.47	0.53	0.98	1.30	4.33	0.49*1.16	2.20	8,800
	1/2"	CBX13SF	2.01	1.57	0.59	0.67	1.18	1.57	5.35	0.63*1.45	3.75	15,000
	5/8"	CBX16SF	2.20	1.77	0.71	0.87	1.46	1.89	6.10	0.82*2.02	7.05	22,600
	3/4"	CBX20SF	2.36	2.09	0.91	0.98	2.01	2.05	7.28	0.94*2.87	11.02	35,300
	7/8"	CBX22SF	2.60	2.44	0.98	1.26	1.97	2.48	8.27	1.02*2.83	27.12	42,700

Clevis Sling Hook, Grade 100 without latch


	For Chain	Code	Dimensions						Weight/ea, lbs	Work Load Limit, lbs	
			A	B	C	G	H	R			PxL
	9/32"	CBX07	1.34	0.37	0.39	0.75	1.10	3.74	0.35*0.90	1.21	4,300
	5/16"	CBX08	1.34	0.37	0.39	0.75	1.10	3.74	0.35*0.90	1.21	5,700
	3/8"	CBX10	1.57	0.47	0.53	0.98	1.30	4.33	0.49*1.16	2.20	8,800
	1/2"	CBX13	2.01	0.59	0.67	1.18	1.57	5.35	0.63*1.45	3.75	15,000
	5/8"	CBX16	2.20	0.71	0.87	1.46	1.89	6.10	0.82*2.02	7.05	22,600

Never exceed work load limit. Always follow your domestic safety regulations.


NORTHERN STRANDS

Alloy Chain Fittings Grade 100


Clevis Grab Hook with Saddle, and Space for Latch, Grade 100

	For Chain	Code	Dimensions							PxL	Weight/ea, lbs	Work Load Limit, lbs
			A	B	C	G	H	R	M			
	9/32"	CFX07	0.39	0.39	0.45	1.18	1.10	2.57	1.85	0.35*0.90	0.97	4,300
	5/16"	CFX08	0.39	0.39	0.43	1.18	1.10	2.56	1.85	0.39*0.90	0.97	5,700
	3/8"	CFX10	0.51	0.51	5.87	1.34	1.34	3.15	2.17	0.51*1.24	2.12	8,800
	1/2"	CFX13	0.67	0.67	6.85	1.85	1.85	4.15	3.19	0.63*1.65	4.63	15,000
	5/8"	CFX16	0.75	0.75	0.72	2.52	2.52	4.40	3.62	0.82*2.02	7.50	22,600
	3/4"	CFX20	0.93	0.91	0.87	3.31	2.56	4.65	3.94	0.94x2.42	11.46	35,300
	7/8"	CFX22	1.02	1.02	0.98	3.62	2.56	6.06	4.72	1.02x2.83	17.20	42,700


Clevis Grab Hook with Saddle, and Latch, Grade 100

	For Chain	Code	Dimensions							PxL	Weight/ea, lbs	Work Load Limit, lbs
			A	B	C	G	H	R	M			
	9/32"	CFX07S	0.39	0.39	0.45	1.18	1.10	2.57	1.85	0.35*0.90	0.97	4,300
	5/16"	CFX08S	0.39	0.39	0.43	1.18	1.10	2.56	1.85	0.39*0.90	0.97	5,700
	3/8"	CFX10S	0.51	0.51	5.87	1.34	1.34	3.15	2.17	0.51*1.24	2.12	8,800
	1/2"	CFX13S	0.67	0.67	6.85	1.85	1.85	4.15	3.19	0.63*1.65	4.63	15,000
	5/8"	CFX16S	0.75	0.75	0.72	2.52	2.52	4.40	3.62	0.82*2.02	7.50	22,600


Clevis Self Locking Hook, Grade 100

	For Chain	Code	Dimensions							PxL	Weight/ea, lbs	Work Load Limit, lbs
			A	B	C	G	H	R	T			
	9/32"	CRFX07	1.34	0.35	0.39	0.79	1.02	4.84	1.69	0.35*0.90	2.09	4,300
	5/16"	CRFX08	1.77	0.35	0.39	0.79	1.02	4.84	1.69	0.39*0.90	2.09	5,700
	3/8"	CRFX10	1.77	0.47	0.55	0.98	1.18	5.63	2.20	0.51*1.24	3.53	8,800
	1/2"	CRFX13	2.01	0.59	0.67	1.38	1.57	7.09	2.72	0.63*1.65	7.05	15,000
	5/8"	CRFX16	2.36	0.75	0.75	1.42	1.97	8.46	3.15	0.82*2.02	13.23	22,600

Shortening Clutch, Grade 100

	For Chain	Code	Dimensions							PxL	Weight/ea lbs	Work Load Limit lbs
			A	B	C	D	E	F	G			
	9/32"	CXX07	0.37	0.37	0.39	0.37	0.93	2.20	1.14	0.35x0.89	1.06	4,300
	5/16"	CXX08	0.37	0.37	0.39	0.37	0.93	2.20	1.14	0.39x0.89	1.06	5,700
	3/8"	CXX10	0.47	0.47	0.57	0.47	1.28	3.07	1.42	0.51x1.24	2.47	8,800
	1/2"	CXX13	0.61	0.61	0.71	0.61	1.73	3.54	1.38	0.63x1.65	4.03	15,000
	5/8"	CXX16	0.75	0.83	0.83	0.75	1.97	4.17	1.50	0.83x1.65	6.24	22,600

Eye Sling Hook with Forged Latch, Grade 100

	For Chain	Code	Dimensions							Weight/ea, lbs	Work Load Limit, lbs
			A	A1	D	G	H	O	R		
	9/32"+5/16"	CAX08SF	1.30	0.98	0.43	0.75	1.14	0.98	3.98	1.10	5,700
	3/8"	CAX10SF	1.57	1.26	0.63	1.02	1.30	1.34	5.16	2.14	8,800
	1/2"	CAX13SF	2.01	1.61	0.75	1.30	1.65	1.69	6.26	4.19	15,000
	5/8"	CAX16SF	2.20	1.81	0.96	1.57	1.97	1.97	7.20	7.28	22,600
	3/4"	CAX20SF	2.28	2.05	1.06	1.89	2.09	2.17	7.99	9.92	35,300
	7/8"	CAX22SF	2.64	2.44	1.14	1.97	2.36	2.36	8.82	15.65	42,700

Never exceed work load limit. Always follow your domestic safety regulations.