

HAND WINCH

VITALI-INTL®

VITALI-INTL® Hand Winch

Backward & Forward lever – placed in tandem providing a slim design and assuring power transfer along the center.

Built-in shearing pin – prevent overload. It functions at approx. 25% overload. The pins can be replaced without removing the load.

Safety pin – fastens the anchor bolt.

Anchor bolt – offers numerous and versatile connection possibilities with load hooks, sling ropes and sling chains.

Spare shear pins – Two pieces of spare shear pins located in the carrying handle.

Rope clamp system – easily disengaged with a lever allowing smooth installation of the wire rope.

High strength cast aluminum alloy body – Light weight, simple to operate. Smooth contour design with large, flat bottom surface for increased stability in horizontal as well as vertical working position.

Stamped serial number – for easy identification

Galvanized steel wire rope mounted on a reel – Every rope is operationally tested to 150% of the rated capacity and is issued with an individual test certificate.



MODEL NO.		YAL008	YAL016	YAL032
Lifting Capacity (Rated Load)	(tonnes)	0.8	1.6	3.2
*Pulling Capacity	(tonnes)	1.2	2.4	4
Lever Pull at Rated Load	(N)	284	412	441
Forward Travel	(mm)	52	55	28
Wire Rope Diameter	(mm)	8.3	11	16
Net Weight (Body)	(kg)	6.4	12.4	23.3
Net Weight (20 metres Wire Rope)	(kg)	7	11.5	23.5
Net Weight (Lever Handle)	(kg)	1.15	2.5	2.5
Dimensions (Body) L x W x H	(mm)	440 x 70 x 255	560 x 100 x 295	675 x 120 x 350

*Observe local regulations

SASKATOON - 3235 Millar Avenue, Saskatoon SK S7K 5Y3
 FAX: (306) 249-4374 **Ph: (306) 242-7073** Toll Free: 1-800-242-7073
 email: sales@northernstrands.com

REGINA - 125 Henderson Drive, Regina SK S4N 5W4
 FAX: (306) 352-9112 **Ph: (306) 352-7073** Toll Free: 1-800-242-7073
 email: sales@northernstrands.com