

FOR THOSE BIG TOW JOBS

8 STRAND TOW ROPE



Our premium 8 Strand Tow rope is manufactured from high tenacity polypropylene yarns, Superdan offers easy handling, high strength and excellent abrasion resistance.

Features:

- Excellent anti-abrasion properties contribute to longer working life
- High UV light resistance
- Highly flexible, easy to handle
- 50% better breaking strength compared to BS and ISO standards

Applications:

- Mooring lines
- General and commercial fishing rope
- Anchor lines
- Equipment towing
- Tractor towing

Technical Specs:

- Class II Rope
- Specific Gravity: 0.91
- Elastic Elongation Percentage: At % of breaking strength – 20-22%
- Splicing Procedures Required
- Eye splice – 8-strand/Class II Rope
- End for End splice – 8-strand/Class II Rope

Dia.	Circ.	Dia. mm	Weight per 100 ft.	Min. Break Strength/LBS
1-5/8"	5	40	53.1	62,500
2"	6	48	80.2	91,400
2-1/4"	7	56	108.5	120,600
2-5/8"	8	64	141.1	155,000
3"	9	72	178.1	197,100

SASKATOON

3235 Millar Avenue, Saskatoon SK S7K 5Y3 FAX: (306) 249-4374
Ph: (306) 242-7073 Toll Free: 1-800-242-7073

REGINA

125 Henderson Drive, Regina SK S4N 5W4 FAX: (306) 352-9112
Ph: (306) 352-7073 Toll Free: 1-800-242-7073