

NORTHERN STRANDS



Durastat™ Double Braid Polyester

Stability, strength, and durability are maximized with a braid on braid polyester. Excellent dielectric strength. Meets or exceeds US. Military Specifications # Mil-STL-24677B and Canadian Military Specifications 40-16-95 Type 3. Specific Gravity 1.38. Standard White/Green Tracer

KEY BENEFITS:

- Low Stretch
- High Tensile Strength
- Ideal for most Industrial Applications

Diameter	Diameter in MM	Circumference	LBS/100 Feet	KGS/100 Meters	Approx. Tensile in LBS	Approx. Tensile In KG
1/4"	6	3/4"	2.00	3.0	1900	856
5/16"	8	1	3.10	4.6	3200	1441
3/8"	10	1 1/8"	4.30	6.4	4200	1892
7/16"	11	1 5/16"	6.20	9.2	6000	2703
1/2"	12	1 1/2"	8.20	12.3	7500	3378
9/16"	14	1 3/4"	9.50	14.1	9500	4279
5/8"	16	2"	12.80	19.1	12700	5721
3/4"	18	2 1/4"	17.00	25.3	18800	8468
7/8"	22	2 3/4"	23.20	34.5	27660	12459
1"	24	3"	30.20	44.9	31000	13964
1 1/8"	28	3 1/2"	39.20	58.3	40650	18311
1 1/4"	30	3 3/4"	47.50	70.7	49000	22072
1 5/16"	32	4"	55.00	81.8	55000	24775
1 1/2"	36	4 1/2"	68.00	101.2	70500	31725
1 5/8"	40	5"	82.00	122.0	89600	33558
1 3/4"	44	5 1/2"	95.00	141.4	103800	38626
2"	48	6"	124.00	184.5	126000	46846
2 1/8"	50	6 1/2"	137.00	203.9	143000	64414
2 1/4"	56	7"	153.00	227.7	160000	72072
2 1/2"	60	7 1/2"	189.00	281.3	181000	81531



Nylon Shock Cord

Multiple uses, with the most common, being used as a door latch for cages. High quality nylon, and heavy duty recover. Excellent abrasion resistance.

KEY BENEFITS:

- Heavy Duty Recovery
- High Durability
- U.V. Stabilized.

DIA	FT. SPOOL	LBS. PER SPOOL
1/4"	500	12
5/16"	500	16
3/8"	250	12