





POLYESTER ROUND SLINGS					
Table I: Rated Capacity for Polyester Round slings					
Round sling Size / #		 Vertical	 Choker	 Vertical Basket	 45° Basket
	Color*	Pounds	Pounds	Pounds	Pounds
NS3	Purple	3000	2400	6000	4242
NS4	Black	4000	3200	8000	5656
NS6	Green	6000	4800	12000	8484
NS9	Yellow	9000	7200	18000	12726
NS12	Tan	12000	9600	24000	16968
NS14	Red	14000	11200	28000	19796
NS17	Orange	17000	13600	34000	24038
NS23	Blue	23000	18400	46000	32522
NS26	Orange	26000	20800	52000	36764
NS32	Grey	32000	25600	64000	45248
NS40	Orange	40000	32000	80000	56560
NS54	Brown	54000	43200	108000	76356
NS68	Olive	68000	54400	136000	98980
NS90	Black	90000	72000	180000	127260

NOTE: DESIGN FACTOR = 5 : 1 WARNING: DO NOT EXCEED RATED CAPACITIES

FOR LARGER CAPACITIES PLEASE INQUIRE

*** Caution:** Color Code and rated capacities may vary among manufacturers. Always check the identification tag to determine if the polyester round sling rated capacity is applicable for the lift.

INSPECTION/REMOVAL CRITERIA

SLING SHALL BE REMOVED FROM SERVICE IF ANY DEFECTS SUCH AS THE FOLLOWING ARE VISIBLE:

- A Acid or alkali.
- B Melting, charring or weld splatter on any part of the sling.
- C Holes, tears, cuts, abrasive wear, or snags that expose the lead carrying yarns.
- D Broken or worn stitching in cover.
- E Fittings that are permanently attached to the sling are damaged, stretched or distorted in any way.
- F Knots in any part of the sling.
- H If sling identification tag is missing or unreadable.